



Nam Bee Pro-Miler® Solid Tyres



Technical Specifications

(wef : 1st Oct 2024)

Tyre Size	Rim Size	Tread Pattern	Tread Depth	Tyre Width	Tyre Diameter	Forklift Truck Load Capacity		Weight
						(Speed 25 Km/h Max)		
						Load Wheel	Steering Wheel	
			(mm)	(mm)	(mm)	(kg)	(kg)	(kg)
4.00-8	3.00D-8	Super Rib	8	103	400	950	730	10.6
5.00-8	3.00D-8	Super Grip	15	125	440	1415	1090	15.7
16x6-8 (150/75-8)	4.33R-8	Super Grip	18	154	410	1495	1150	16.2
18x7-8 (180/70-8)	4.33R-8	Super Grip	21	152	448	2145	1650	19.1
6.00-9	4.00E-9	Super Grip	20	135	513	1885	1450	24.0
21x8-9	6.00E-9	Super Grip	22	180	519	2755	2120	32.6
6.50-10	5.00F-10	Super Grip	20	163	566	2340	1800	35.0
23x9-10 (225/75-10)	6.50F-10	Super Grip	22	200	580	3445	2650	44.0
7.00-12	5.00S-12	Super Grip	22	171	646	2920	2240	46.0
27x10-12 (250/75-12)	8.00G-12	Super Grip	Coming Soon					
7.00-15	5.50-15	Super Grip	24	174	718	3545	2725	54.0
	6.00-15	Super Grip	24	174	718	3545	2725	54.6
8.15-15 (28x9-15 / 225/75-15)	7.00-15	Super Grip	24	222	702	3945	2650	63.0
8.25-15	6.50-15	Super Grip	27	224	802	4750	3650	92.0
2.50-15 (250/70-15)	7.00-15	Super Grip	21	214	705	4750	3650	61.7
	7.50-15	Super Grip	21	214	705	4750	3650	62.8
3.00-15 / 315/70-15	8.00-15	Super Grip	32	252	812	5850	4500	104.0
9.00-20	6.50-20	Super Grip	25	240	970	5400	4500	138.0
	7.00-20	Super Grip	25	240	970	5400	4500	138.8
10.00-20	7.50-20	Super Slick	-	256	1174	6000	5000	168.0

* Please allow for commercial tolerance of 3%.



Super Rib



Super Grip



Super Slick